


## DOOR BOTTOM SEALS

# LAS3009 si

## MEDIUM DUTY

Medium duty door bottom seal with slide-in gaskets. Suitable for single and double swing doors, or to use as meeting stiles (one leaf only).



▲  
LAS3009 si



DOOR BOTTOM SEALS

▲  
LAS3009 si  
shown with LAS4002

## SYSTEM SPECIFICATIONS

### Key benefits

- ▶ Simple, effective sealing solution.
- ▶ Easily retrofitted to existing door assemblies.
- ▶ Durable, hard wearing silicone rubber gaskets.
- ▶ Protects against sound, smoke, weather, draught, light and insects.

### Gap size

- ▶ 12mm/18mm.

### Standard lengths

- ▶ 1m and 2.1m.
- ▶ Other lengths available to special order.

### Approvals

- ▶ **Smoke:** Conforms with BCA Specification C3.4 smoke sealing requirements.
- ▶ **Durability:** Long term mechanical test, completing 100,000 cycles without failure.

### Fixing method

- ▶ Face-fixed, semi-rebated or fully rebated.
- ▶ Fixing screws are supplied.
- ▶ Fixing holes are pre-drilled.
- ▶ Once the aluminium carrier is fixed, the rubber gasket slides easily into place.
- ▶ Note: these seals cannot be adjusted once fitted.

### Finishes

- ▶ Silver anodised aluminium with grey silicone rubber insert.