


Fitting instructions

Door bottom seal

LAS3009 si



Length:

Contents include

Aluminium carrier with pre-drilled holes Bag of screws
Fitting instructions

Tools required

Saw (power or hand)
Screw driver
Drill (power or hand)
Knife
Pencil or Marker
Router

For further information about our products please visit our website

www.lorient.com.au

t: +61 (02) 9905 0868

e: sales@lorientau.com.au

Instructions

1. If the door is installed, remove from its hinges, lay on its edge and firmly restrain.

If rebating is required:
2. Measure and mark out the seal position along the centre line of the door stile/ bottom. (Note that the finished groove should be 35mm wide).
3. Fit a suitable cutter into the router, set guide and machine a 5mm deep groove along the edge/bottom of the door.
4. Clean dust and chips from the groove and check depth by applying seal.

Please note: *Recommendations as to methods, use of materials and construction details are based on the experience and knowledge of Lorient and are given in good faith as a general guide and service to designers, contractors and manufacturers.*

Lorient reserves the right to make alterations or delete installation detail without prior notice.

5. Measure the door width and cut the seal to suit, using a sharp knife for the silicone gasket and a saw for the aluminum section.
6. Replace silicone gasket and screw fix the aluminium section into the groove using the screws supplied (fixing holes are pre-drilled).
7. Ends of the aluminium channel may be centre punched to prevent gasket movement.



Important

Ensure that the installation of this product does not impede the opening or closing of the door. It is recommended to check the adjustment of the door seal periodically to ensure the door assembly to which it is fitted, closes and latches properly.

We recommend the LAS3009 si be used together with a Lorient threshold plate.

Other Lorient products:

Acoustic, smoke & fire seals
Fire resistant glazing systems
Fire resistant door hardware
Air transfer grilles/ dampers
Georgia Pacific doors