

Aeron® Selection Chart



These results are based on a standard residential sash of 0.65kg per linear metre.
Non friction Interlock stays must be used. It is recommended that sash widths above 900mm use two actuators to achieve full window seal

4mm Glass

		Sash Width (mm)					
Sash Height (mm)		600	900	1200	1500	1800	2400
	300	1	1	2	2	2	2
	400	1	1	2	2	2	2
	500	1	1	2	2	2	2
	600	1	1	2	2	2	2
	700	1	1	2	2	2	2
	800	1	1	2	2	2	2
	900	1	1	2	2	2	2
	1000	1	1	2	2	2	2
	1100	1	1	2	2	2	2
	1200	1	1	2	2	2	2
	1300	1	1	2	2	2	2
	1400	1	1	2	2	2	2
	1500	1	1	2	2	2	2
	1800	1	1	2	2	2	2

5mm Glass

		Sash Width (mm)					
Sash Height (mm)		600	900	1200	1500	1800	2400
	300	1	1	2	2	2	2
	400	1	1	2	2	2	2
	500	1	1	2	2	2	2
	600	1	1	2	2	2	2
	700	1	1	2	2	2	2
	800	1	1	2	2	2	2
	900	1	1	2	2	2	2
	1000	1	1	2	2	2	2
	1100	1	1	2	2	2	2
	1200	1	1	2	2	2	2
	1300	1	1	2	2	2	2
	1400	1	1	2	2	2	2
	1500	1	1	2	2	2	2
	1800	1	1	2	2	2	2

6mm Glass

		Sash Width (mm)					
Sash Height (mm)		600	900	1200	1500	1800	2400
	300	1	1	2	2	2	2
	400	1	1	2	2	2	2
	500	1	1	2	2	2	2
	600	1	1	2	2	2	2
	700	1	1	2	2	2	2
	800	1	1	2	2	2	2
	900	1	1	2	2	2	2
	1000	1	1	2	2	2	2
	1100	1	1	2	2	2	2
	1200	1	1	2	2	2	2
	1300	1	1	2	2	2	2
	1400	1	1	2	2	2	2
	1500	1	1	2	2	2	2
	1800	1	1	2	2	2	2

8mm Glass

		Sash Width (mm)					
Sash Height (mm)		600	900	1200	1500	1800	2400
	300	1	1	2	2	2	2
	400	1	1	2	2	2	2
	500	1	1	2	2	2	2
	600	1	1	2	2	2	2
	700	1	1	2	2	2	2
	800	1	1	2	2	2	2
	900	1	1	2	2	2	2
	1000	1	1	2	2	2	2
	1100	1	1	2	2	2	2
	1200	1	1	2	2	2	2
	1300	1	1	2	2	2	2
	1400	1	1	2	2	2	2
	1500	1	2	2	2	2	2
	1800	1	2	2	2	2	2

10mm Glass

		Sash Width (mm)					
Sash Height (mm)		600	900	1200	1500	1800	2400
	300	1	1	2	2	2	2
	400	1	1	2	2	2	2
	500	1	1	2	2	2	2
	600	1	1	2	2	2	2
	700	1	1	2	2	2	2
	800	1	1	2	2	2	2
	900	1	1	2	2	2	2
	1000	1	1	2	2	2	2
	1100	1	1	2	2	2	2
	1200	1	1	2	2	2	2
	1300	1	2	2	2	2	2
	1400	1	2	2	2	2	2
	1500	1	2	2	2	2	2
	1800	2	2	2	2	2	2

12mm Glass

		Sash Width (mm)					
Sash Height (mm)		600	900	1200	1500	1800	2400
	300	1	1	2	2	2*	2*
	400	1	1	2	2	2	2
	500	1	1	2	2	2	2
	600	1	1	2	2	2	2
	700	1	1	2	2	2	2
	800	1	1	2	2	2	2
	900	1	1	2	2	2	2
	1000	1	1	2	2	2	2
	1100	1	2	2	2	2	2
	1200	1	2	2	2	2	2
	1300	1	2	2	2	2	2
	1400	1	2	2	2	2	2
	1500	1	2	2	2	2	2
	1800	2	2	2	2	2	2

*Restrict chain to 200mm or less. Outside of stay capacity, still within actuator limit.

- Restrict chain to 200mm or less
- Outside of stay capacity but within actuator limit
- Can not be used as sash is too heavy for window stay and actuator

ASSA ABLOY New Zealand Ltd.
PO Box 100407, North Shore
Auckland 0745

6 Armstrong Road, Albany
Auckland 0632
New Zealand

Tel: +64 9 415 7888
Fax: +64 9 415 7889
Website: www.yalehome.com/nz

ASSA ABLOY Australia Pty Ltd.

235 Huntingdale Road,
Oakleigh 3166, Australia

Tel: 1300 LOCK UP (1300 562 587)
Website: www.yalehome.com/au

Part of ASSA ABLOY

Aeron® Selection Chart



These results are based on a standard residential sash of 0.65kg per linear metre.
Non friction Interlock stays must be used. It is recommended that sash widths above 900mm use two actuators to achieve full window seal

16mm Glass

		Sash Width (mm)					
Sash Height (mm)		600	900	1200	1500	1800	2400
	300	1	1	2	2*	2*	
	400	1	1	2	2	2	
	500	1	1	2	2	2	
	600	1	1	2	2	2	
	700	1	1	2	2	2	
	800	1	2	2	2	2	
	900	1	2	2	2	2	
	1000	1	2	2	2	2	
	1100	1	2	2	2	2	
	1200		2	2	2	2	
	1300		2	2	2	2	
	1400		2	2	2	2	
	1500		2	2	2	2	
	1800		2	2	2	2	

24mm Glass

		Sash Width (mm)					
Sash Height (mm)		600	900	1200	1500	1800	2400
	300	1	2	2*			
	400	1	2	2			
	500	1	2	2	2		
	600	1	2	2	2		
	700	1	2	2	2		
	800		2	2	2		
	900		2	2	2		
	1000		2	2	2		
	1100		2	2	2		
	1200		2	2	2		
	1300		2	2	2		
	1400		2	2	2		
	1500		2	2	2		
	1800		2	2	2		

28mm Glass

		Sash Width (mm)					
Sash Height (mm)		600	900	1200	1500	1800	2400
	300	1*	2*	2*			
	400	1	2	2			
	500	1	2	2			
	600	1	2	2			
	700		2	2			
	800		2	2			
	900		2	2			
	1000		2	2			
	1100		2	2			
	1200		2	2			
	1300		2	2			
	1400		2	2			
	1500		2	2			
	1800		2	2			

Stay	Stay Height	Model	Max. Weight (kg)	Restriction
A Stay	300	230 NF	10	200mm
Nexus	300	240N	18	150mm
4B	300	200 4B NF	10	200mm
4B	400	350 4B NF	20	200mm
4B	500	500 4B NF	30	200mm

*Restrict chain to 200mm or less. Outside of stay capacity, still within actuator limit.

- Restrict chain to 200mm or less
- Outside of stay capacity but within actuator limit
- Can not be used as sash is too heavy for window stay and actuator

ASSA ABLOY New Zealand Ltd.
PO Box 100407, North Shore
Auckland 0745

6 Armstrong Road, Albany
Auckland 0632
New Zealand

Tel: +64 9 415 7888
Fax: +64 9 415 7889
Website: www.yalehome.com/nz

ASSA ABLOY Australia Pty Ltd.

235 Huntingdale Road,
Oakleigh 3166, Australia

Tel: 1300 LOCK UP (1300 562 587)
Website: www.yalehome.com/au

Part of ASSA ABLOY