

## DOOR BOTTOM SEALS


# LAS3001 si & LAS3002 si

## MEDIUM DUTY

Medium duty door bottom and meeting stile seals with slide-in gaskets; ideal for acoustic and smoke containment.



### DOOR BOTTOM SEALS



LAS3001 si

LAS3002 si



LAS3001 si

## SYSTEM SPECIFICATIONS

### Key benefits

- ▶ Simple, effective sealing solution.
- ▶ Easily retrofitted to existing door assemblies.
- ▶ Durable, hard wearing silicone rubber gaskets.
- ▶ Protects against sound, smoke, weather, draught, light and insects.

### Gap size

- ▶ LAS3001 si – 6mm/13mm.
- ▶ LAS3002 si – 10mm/17mm.

### Standard lengths

- ▶ 2.1m.
- ▶ Other lengths available to special order.

### Approvals

- ▶ **Smoke:** Conforms with BCA Specification C3.4 smoke sealing requirements.
- ▶ **Sound:** BS EN ISO 10140-2: 2010. LAS3001 si: Rw 32dB, LAS3002 si: Rw 31dB.
- ▶ **Durability:** Long term mechanical test, completing 100,000 cycles without failure.

### Fixing method

- ▶ Face-fixed, semi-rebated or fully rebated.
- ▶ Fixing screws are supplied.
- ▶ Fixing holes are pre-drilled.
- ▶ Once the aluminium carrier is fixed, the rubber gasket slides easily into place.
- ▶ Note: these seals cannot be adjusted once fitted.

### Finishes

- ▶ Silver anodised aluminium with grey silicone rubber insert.